



THIS DRAWING INDICATES SIZES AND LOADS TO ALLOW FOR INSTALLATION OF METSO MINERALS EQUIPMENT.

METSO MINERALS CANNOT BE LIABLE FOR:

- CONCRETE WORKS SHOWN IN THIS DRAWING AS THEIR DESIGN, CALCULATION AND EXECUTION ARE CUSTOMER'S RESPONSIBILITY.
- NATURE AND ADMISSIBLE PRESSURE OF THE GROUND WHICH MUST BE CHECKED BY THE CUSTOMER ACCORDING TO INDICATED LOADS.
- LOADS APPLIED BY EQUIPMENT NOT SUPPLIED BY METSO MINERALS, MAKE SURE THAT NO RE-BARS ARE LOCATED DIRECTLY UNDERNEATH THE FOOT PLATES TO ALLOW DRILLING HOLES NEEDED TO INSTALL THE EXPANSION BOLTS.

DEMANDS ON FOUNDATION:

- MAXIMUM RELATIVE SUPPORT SUBSIDENSE IS 10mm.
- MAXIMUM SUPPORT SUBSIDENSE DIFFERENCE BETWEEN PLINTHS ON THE SAME SIDE IS 5mm.

THE CONCRETE SLABS ACCESS STAIRS ARE NOT DEFINED IN THIS FOUNDATION DRAWING. THE CONCRETE SLABS MUST BE DONE ON THE CUSTOMER'S RESPONSIBILITY AND AFTER ERECTION.

FOUNDATION DRAWING
 NOTE: UNLESS OTHERWISE INDICATED ALL THE FOUNDATIONS ON LEVEL ±0,00mm

NO	DESCRIPTION OF CHANGES	BY	DATE
1	ISSUED FOR CONSTRUCTION	MM	2024

DATE	BY	DESCRIPTION
01.09.2024	MM	ISSUED FOR CONSTRUCTION

PROJECT	FOUNDATION AND LOADS
CLIENT	NEFTGAZKHONDAZ BOOZJI
SCALE	1/1
DATE	01.09.2024

NO	DATE	BY
1	01.09.2024	MM

metso

MM1081934